

# cutting instructions roller fabrics

<b>Delivery for shipment</b>	Roller fabric is wound on a spiral wound tube with an inside diameter of 76 mm and a width of at least 230 cm. It is wrapped in blister packing and packaged in cardboard packaging.
<b>Fabric length</b>	25 metres per roll (+/- 20%)
<b>Width</b>	230 cm (+/- 10 mm). Deviant length and width upon request.
<b>Weight</b>	Max. 25 kg per packaging unit.
<b>Faults</b>	Max. 8 local faults < 20 cm per roll, indicated with a red fault sticker on the side. Reimbursement 20 cm per fault. Faults longer than 20 cm are grossed up according to length.
<b>Inspection report</b>	With each roll, specifying type and location of the fault.
<b>Maximum cutting height</b>	260 cm
<b>Maximum cutting width</b>	230 cm
<b>Application</b>	For indoor use as a roller blind in combination with suitable hardware.
<b>Storage</b>	In order to preserve the characteristics of the bolt, store it in the original packaging in a horizontal position at a relative atmospheric humidity level of approx. 60%.
<b>Cutting instructions assembly</b>	Weft direction is in the width of the roller fabric. Warp direction is in the height of the roller blind (note: specified on the roller fabric with a sticker). Unrolling direction outside is window side of the roller fabric.
<b>Product specifications</b>	Cloth width +/- 10 mm Weft deviation max. 2% cloth width Bulging (convex / concave) max. 10 mm side / middle / side Twisting max. 10 mm side / middle / side
<b>Deformation/shrinkage/ hanging behaviour</b>	DIN ISO EN 25077
<b>Assembly/Cutting</b>	Use a suitable cutting and unrolling device of sufficient size and quality. Utilise cutting equipment which does not produce fraying, or an uneven cut. Suitable cutting techniques are, among others: ultrasonic and cutting/sealing by means of heat. Settings may differ per cutting device; consult the instructions of your machine supplier.
<b>Quality</b>	Quality inspection, min. 24 hours after assembly.
<b>Cleaning/washing</b>	Wipe softly using an anti-static cloth or brush; any further cleaning should be carried out by a specialist.

The logo for Lienesch, featuring the brand name in a red, cursive script font. The word 'Lienesch' is written twice, with the second instance slightly offset and faded behind the first.

w e c a t c h t h e l i g h t

[www.liensch.com](http://www.liensch.com)

Lienesch bv | Elektrostraat 7 | 7483 PG Haaksbergen | The Netherlands | T: +31 535 730 630 | F: +31 535 730 636 | [sales@liensch.com](mailto:sales@liensch.com)